

AS568B	O型圈的尺寸 (单位 : mm)			
公称编号	线径 C/S	内径 d		
001	1.02	0.74	±0.10	
002	1.27	1.07		
003	1.52	1.42		
004	1.78	1.78	±0.12	
005		2.57		
006		2.9		
007		3.68		
008		4.47		
009		5.28		
010		6.07		
011		7.65		
012		9.25		
013		10.82		
014		12.42		
015		14		
016		15.6		
017		17.17		
018		18.77		
019		20.35		±0.15
020		21.95		
021	23.52			
022	25.12			
023	26.7			
024	28.3			
025	29.87			
026	31.47			
027	33.05			
028	34.65			
029	37.82			
030	41			
031	44.17			
032	47.35			
033	50.52			
AS568B	O型圈的尺寸 (单位 : mm)			

AS568B	O型圈的尺寸 (单位 : mm)			
公称编号	线径 C/S	内径 d		
034	1.78	53.7	±0.25	
035		56.87		
036		60.05		
037		63.22		
038		66.4		
039		69.57		
040		72.75		
041		75.92		
042		82.27		
043		88.62		
044		94.97		
045		101.32		
046		107.67		
047		114.02		
048		120.37		
049		126.72		
050		133.07		
AS568B	O型圈的尺寸 (单位 : mm)			
102	±0.07	1.24	±0.12	
103	2.06			
104	2.84			
105	3.63			
106	4.42			
107	5.23			
108	6.02			
109	7.59			
110	9.19			
111	10.77			
112	12.37			
113	13.94			
114	15.54			
115	17.12			
116	18.72			
AS568B	O型圈的尺寸 (单位 : mm)			

AS568B	O型圈的尺寸 (单位 : mm)			
公称编号	线径 C/S	内径 d		
117	2.62	20.29	±0.15	
118		21.89		
119		23.47		
120		25.07		
121		26.64		
122		28.24		
123		29.82		
124		31.42		
125		32.99		
126		34.59		
127		36.17		
128		37.77		
129		39.34		
130		40.94		
131		42.52		
132		44.12		
133		45.69		
134	47.29			
135	48.9	±0.25		
136	50.47			
137	52.07			
138	53.64			
139	55.24			
140	56.82			
141	58.42			
142	59.99			
143	61.6			
144	63.17			
145	64.77			
146	66.34			
147	67.94			
148	69.52			
149	71.12			
AS568B	O型圈的尺寸 (单位 : mm)			

AS568B	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
150	2.62	72.69	±0.38
151		75.87	
152		82.22	
153		88.57	
154		94.92	
155		101.27	
156		107.62	
157		113.97	
158		120.32	
159		126.67	
160		133.02	
161		139.37	
162		145.72	
163		152.07	
164		158.42	
165		164.77	
166		171.12	
167	177.47		
168	183.82		
169	190.17		
170	196.52		
171	202.87		
172	209.22		
173	215.57		
174	221.92		
175	228.27		
176	234.62		
177	240.97		
178	247.32		
169	190.17		
170	196.52		
171	202.87		
172	209.22		
AS568B	O型圈的尺寸 (单位 : mm)		

公称编号	线径 C/S	内径 d
201	3.53 ±0.10	4.34 ±0.12
202		5.94
203		7.52
204		9.12
205		10.69
206		12.29
207		13.87
208		15.47
209		17.04
210		18.64
211		20.22
212		21.82
213		23.39
214		24.99
215		26.57
216		28.17 ±0.15
217		29.74
218		31.34
219		32.92
220		34.52
221		36.09
222		37.69
223		40.87
224	44.04	
225	47.22	
226	50.39	
227	53.57 ±0.25	
228	56.74	
229	59.92	
230	63.09	
231	66.27	
232	69.44 ±0.38	
233	72.62	
AS568B	O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d

公称编号	线径 C/S	内径 d
234	3.53 ±0.10	75.79 ±0.38
235		78.97
236		82.14
237		85.32
238		88.49
239		91.67
240		94.84
241		98.02
242		101.19 ±0.38
243		104.37
244		107.54
245		110.72
246		113.89
247		117.07
248		120.24
249		123.42
250		126.59 ±0.10
251		129.77
252		132.94
253		136.12
254		139.29
255		142.47
256		145.64 ±0.58
257	148.82	
258	151.99	
259	158.34	
260	164.69	
261	171.04	
262	177.39	
263	183.74	
264	190.09 ±0.76	
265	196.44	
266	202.79	
AS568B	O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d

公称编号	线径 C/S	内径 d	
267	3.53 ±0.10	209.14 ±0.76	
268		215.49	
269		221.84	
270		228.19	
271		234.54	
272		240.89	
273		247.24	
274		253.59 ±0.76	
275		266.29	
276		278.99	
277		291.69	
278		304.39	
279		329.79	
280		355.19	
281		380.59	
282		405.26 ±1.14	
283		430.66	
284		456.06	
309		5.33 ±0.12	10.46 ±0.12
310			12.06
311			13.64
312			15.24
313			16.81
314	18.42		
315	19.99		
316	21.59		
317	23.16		
318	24.76 ±0.15		
319	26.34		
320	27.94		
321	29.51		
322	31.12		
323	32.69		
AS568B	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	

公称编号	线径 C/S	内径 d
324	5.33 ±0.12	34.29 ±0.15
325		37.46
326		40.64
327		43.82
328		46.99
329		50.16 ±0.25
330		53.34
331		56.52
332		59.69
333		62.86
334	66.04	
335	69.22	
336	72.39	
337	75.56	
338	78.74	
339	81.92	
340	85.09	
341	88.26	
342	91.44	
343	94.62	
344	97.79 ±0.38	
345	100.96	
346	104.14	
347	107.32	
348	110.49	
349	113.66	
350	116.84	
351	120.02	
352	123.19	
353	126.36	
354	129.54 ±0.58	
355	132.72	
356	135.89	
AS568B	O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d

357			139.07		390			532.26	±1.14	452		±0.15	291.46	±0.76	911			21.92	±0.12
358			142.24		391			557.66		453			304.16		912			23.47	
359			145.42		392			582.68		454			316.86		913	2.95		25.04	
360			148.59		393	5.33	±0.12	608.08		455			329.56		914			26.59	±0.15
361			151.77	±0.58	394			633.48	±1.52	456			342.26		916			29.74	
362			158.12		395			658.88		457			354.96		918			34.42	
363			164.47		425			113.66		458			367.66		920			37.46	
364			170.84		426			116.84		460			380.36		924	3		43.69	±0.25
365			177.17		427			120.02	±0.38	461			405.26		928			53.09	
366			183.52		428			123.19		462			417.96		932			59.36	
367			189.87		429			126.36		463			430.66						
368			196.22		430			129.54		464	6.99		443.36						
369			202.57		431			132.72		465			456.06						
370			208.92		432			135.89		466			468.76	±1.14					
371			215.26		433			139.06		467			481.46						
372			221.62		434			142.24		468			494.16						
373	5.33	±0.12	227.96		435			145.42	±0.58	469			506.86						
374			234.32		436			148.59		470			532.46						
375			240.67	±0.76	437			151.76		471			557.66						
376			247.02		438	6.99	±0.15	158.12		472			582.68						
377			253.37		439			164.46		473			608.08	±1.52					
378			266.07		440			170.82		474			633.48						
379			278.77		441			177.16		475			658.88						
380			291.47		442			183.52		901	1.42		4.7	±0.12					
381			304.17		443			189.86		902	1.63		6.07						
382			329.57		444			196.22		903			7.64						
383			354.97		445			202.56		904	1.83		8.92						
384			380.37		446			215.26		905			10.52						
385			405.26		447			227.96	±0.76	906	1.98	±0.07	11.89						
386			430.66		448			240.66		907	2.08		13.46						
387			456.06	±1.14	449			253.36		908	2.21		16.36						
388			481.46		450			266.06		909	2.46		17.93						
389			506.86		451			278.76		910			19.18						

(单位 : 毫米/mm)

: 其他尺寸亦可提供 !

订货示例 :

O型圈 美国标准AS586B 标准号008

内径 (ID)4.47mm

线径 (C/S)1.78mm

材料 : Viton75B (氟橡胶75度黑)

订货号 : ORAR00008-V75B

