

JIS-V	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*V 10	4	±0.10	9.5
*V 11			10.5
*V 12			11.5 ±0.20
*V 14			13.5
V 15			14.5
*V 16			15.5
*V 18			17.5
*V 20			19.5 ±0.24
*V 21			20.5
*V 22			21.5
V 24			23.5
*V 25			24.5
*V 26			25.5
*V 28			27.5 ±0.33
*V 30			29.5
*V 32			31.5
*V 34			33.5
*V 35			34.5
*V 36			35.5 ±0.37
*V 38			37.5
V 40			39.5
*V 42			41.5
*V 44			43.5
*V 45			44.5
*V 46			45.5 ±0.49
*V 48			47.5
*V 50			49.5
*V 53			52.5
V 55			54.5
*V 56			55.5
*V 58			57.5 ±0.61
*V 60			59.5
*V 63			62.5

JIS-V	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*V 65	4	±0.10	64.5
*V 67			66.5 ±0.61
V 70			69.0
*V 75			74.0
*V 80			79.0 ±0.72
V 85			84.0
*V 90			89.0
*V 95			94.0 ±0.83
V 100			99.0
*V 105			104.0
*V 110			109.0
*V 115			114.0 ±0.97
V 120			119.0
*V 125			124.0
*V 130			129.0
*V 135			134.0
*V 140			138.5 ±1.18
*V 145			143.5
V 150			148.5
*V 155			153.0
*V 160			158.0
*V 165			163.0 ±1.36
*V 170	168.0		
V 175	173.0		
*V 180	178.0		
*V 185	183.0		
*V 190	188.0 ±1.53		
*V 195	193.0		
*V 200	198.0		
*V 205	203.0		
*V 210	208.0 ±1.70		
*V 215	213.0		
*V 220	218.0		

JIS-V	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
V 225	6	±0.15	222.5
*V 230			227.5
*V 235			232.5 ±1.95
*V 240			237.5
*V 245			242.5
*V 250			247.5
*V 255			252.5
*V 260			257.5 ±2.02
*V 265			262.5
*V 270			267.5
V 275			272.0
*V 280			277.0
*V 285			282.0
*V 290			287.0 ±2.27
*V 295			292.0
*V 300			297.0
*V 305			302.0
*V 310			307.0
*V 315			312.0 ±2.34
*V 320			317.0
V 325			321.5
*V 330			326.5
*V 335			331.5
*V 340			336.5 ±2.51
*V 345			341.5
*V 350			346.5
*V 355			351.5
*V 360			356.5
*V 365			361.5 ±2.68
*V 370			366.5
*V 375			371.5
V 380			376.0
*V 385			381.0 ±2.83

JIS-V	O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d	
*V 390	6	±0.15	386.0
*V 395			391.0 ±2.83
*V 400			396.0
*V 405			401.0
*V 410			406.0
*V 415			411.0 ±2.99
*V 420			416.0
*V 425			421.0
V 430			425.5
*V 435			430.5
*V 440			435.5 ±3.15
*V 445			440.5
*V 450			445.5
*V 455			450.5
*V 460			455.5
*V 465	460.5 ±3.30		
*V 470	465.5		
*V 475	470.5		
V 480	475.0		
*V 490	485.0		
*V 500	494.5		
*V 510	504.5		
*V 520	514.5		
*V 530	524.5		
*V 540	534.0		
*V 550	544.0 ±3.60		
*V 560	554.0		
*V 570	564.0 ±3.92		
*V 580	574.0		
V 585	579.0		
*V 590	584.0		
*V 600	593.5 ±4.24		
*V 610	603.5		

JIS-V	O型圈的尺寸 (单位 : mm)		内径 d	
公称编号	线径 C/S			
*V 620	10	±0.30	613.5	±4.24
*V 630			623.5	
V 640			633.5	
*V 650			643.0	
*V 660			653.0	
*V 670			663.0	±4.54
*V 680			673.0	
V 690			683.0	
*V 700			692.5	
*V 710			702.5	
*V 720			712.5	±4.83
*V 730			722.5	
V 740			732.5	
*V 750			742.0	
*V 760			752.0	
*V 770			762.0	±5.12
*V 780			772.0	
V 790			782.0	
*V 800			791.5	
*V 810			801.5	
*V 820			811.5	±5.44
*V 830			821.5	
*V 840			831.5	
V 845			836.5	
*V 850			841.5	
*V 860			851.5	
*V 870			861.5	
*V 880			871.5	
*V 890			881.5	±6.06
*V 900			891.0	
*V 910			901.0	
*V 920			911.0	
*V 930			921.0	

JIS-V	O型圈的尺寸 (单位 : mm)		内径 d	
公称编号	线径 C/S			
*V 940	10	±0.30	931.0	±6.06
V 950			940.5	
*V 960			950.5	
*V 970			960.5	
*V 980			970.5	
*V 990			980.5	
*V 1000			990.5	
*V 1010			1000.0	
*V 1020			1010.0	
*V 1030			1020.0	
*V 1040			1030.0	±6.67
*V 1050			1039.0	
V 1055			1044.0	
*V 1100			1089.0	
*V 1150			1139.0	
*V 1200			1189.0	
*V 1250			1239.0	
*V 1300			1289.0	
*V 1350			1339.0	
*V 1400			1389.0	

: 其他尺寸亦可提供 ! (单位 : 毫米/mm)

