

JIS-P		O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d	
*P 2	1.9 ±0.08	1.8 ±0.14	
P 3		2.8 ±0.14	
P 4		3.8 ±0.14	
P 5		4.8 ±0.15	
P 6		5.8 ±0.15	
P 7		6.8 ±0.16	
P 8		7.8 ±0.16	
P 9		8.8 ±0.17	
P 10		9.8 ±0.17	
P 10A		2.4 ±0.09	9.8 ±0.17
P 11	10.8 ±0.18		
P 11.2	11.0 ±0.18		
P 12	11.8 ±0.19		
P 12.5	12.3 ±0.19		
P 14	13.8 ±0.19		
P 15	14.8 ±0.20		
P 16	15.8 ±0.20		
P 18	17.8 ±0.21		
P 20	19.8 ±0.22		
P 21	3.5 ±0.10	20.8 ±0.23	
P 22		21.8 ±0.24	
P 22A		21.7 ±0.24	
P 22.4		22.1 ±0.24	
P 24		23.7 ±0.24	
P 25		24.7 ±0.25	
P 25.5		25.2 ±0.25	
P 26		25.7 ±0.26	
P 28		27.7 ±0.28	
P 29		28.7 ±0.29	
P 29.5	29.2 ±0.29		

JIS-P		O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d	
P 30	3.5 ±0.10	29.7 ±0.29	
P 31		30.7 ±0.30	
P 31.5		31.2 ±0.31	
P 32		31.7 ±0.31	
P 34		33.7 ±0.33	
P 35		34.7 ±0.34	
P 35.5		35.2 ±0.34	
P 36		35.7 ±0.34	
P 38		37.7 ±0.37	
P 39		5.7 ±0.13	38.7 ±0.37
P 40	39.7 ±0.37		
P 41	40.7 ±0.38		
P 42	41.7 ±0.39		
P 44	43.7 ±0.41		
P 45	44.7 ±0.41		
P 46	45.7 ±0.42		
P 48	47.7 ±0.44		
P 49	48.7 ±0.45		
P 50	8.4 ±0.15		49.7 ±0.45
P 48A		47.6 ±0.44	
P 50A		49.6 ±0.45	
P 52		51.6 ±0.47	
P 53		52.6 ±0.48	
P 55		54.6 ±0.49	
P 56		55.6 ±0.50	
P 58		57.6 ±0.52	
P 60		59.6 ±0.53	
P 62		61.6 ±0.55	
P 63	8.4 ±0.15	62.6 ±0.56	
P 65		64.6 ±0.57	

JIS-P		O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d	
P 67	5.7 ±0.13	66.6 ±0.59	
P 70		69.6 ±0.61	
P 71		70.6 ±0.62	
P 75		74.6 ±0.65	
P 80		79.6 ±0.69	
P 85		84.6 ±0.73	
P 90		89.6 ±0.77	
P 95		94.6 ±0.81	
P 100		99.6 ±0.84	
P 102		8.4 ±0.15	101.6 ±0.85
P 105	104.6 ±0.87		
P 110	109.6 ±0.91		
P 112	111.6 ±0.92		
P 115	114.6 ±0.94		
P 120	119.6 ±0.98		
P 125	124.6 ±1.01		
P 130	129.6 ±1.05		
P 132	131.6 ±1.06		
P 135	134.6 ±1.09		
P 140	8.4 ±0.15	139.6 ±1.12	
P 145		144.6 ±1.16	
P 150		149.6 ±1.19	
P 150A		149.5 ±1.19	
P 155		154.5 ±1.23	
P 160		159.5 ±1.26	
P 165		164.5 ±1.30	
P 170		169.5 ±1.33	
P 175		174.5 ±1.37	
P 180		179.5 ±1.40	
P 185	184.5 ±1.44		

JIS-P		O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d	
P 190	8.4 ±0.15	189.5 ±1.48	
P 195		194.5 ±1.51	
P 200		199.5 ±1.55	
P 205		204.5 ±1.58	
P 209		208.5 ±1.61	
P 210		209.5 ±1.62	
P 215		214.5 ±1.65	
P 220		219.5 ±1.68	
P 225		224.5 ±1.71	
P 230		8.4 ±0.15	229.5 ±1.75
P 235	234.5 ±1.78		
P 240	239.5 ±1.81		
P 245	244.5 ±1.84		
P 250	249.5 ±1.88		
P 255	254.5 ±1.91		
P 260	259.5 ±1.94		
P 265	264.5 ±1.97		
P 270	269.5 ±2.01		
P 275	274.5 ±2.04		
P 280	8.4 ±0.15	279.5 ±2.07	
P 285		284.5 ±2.10	
P 290		289.5 ±2.14	
P 295		294.5 ±2.17	
P 300		299.5 ±2.20	
*P 305		304.5 ±2.24	
*P 310		309.5 ±2.27	
P 315		314.5 ±2.30	
P 320		319.5 ±2.33	
*P 325		324.5 ±2.36	

JIS-P O型圈的尺寸 (单位 : mm)			JIS-P O型圈的尺寸 (单位 : mm)			JIS-P O型圈的尺寸 (单位 : mm)			JIS-P O型圈的尺寸 (单位 : mm)					
公称编号	线径 C/S	内径 d	公称编号	线径 C/S	内径 d	公称编号	线径 C/S	内径 d	公称编号	线径 C/S	内径 d			
*P 330	8.4	329.5 ±2.39	*P 480	8.4	479.5 ±3.30	*P 660	8.4	659.5 ±4.70	*P 960	8.4	959.5			
P 335		334.5 ±2.42	*P 485		484.5	*P 670		669.5	*P 970		969.5			
P 340		339.5 ±2.45	*P 490		489.5	*P 680		679.5	*P 980		979.5 ±6.70			
*P 345		344.5 ±2.48	*P 495		494.5	*P 690		689.5	*P 990		989.5			
*P 350		349.5 ±2.51	*P 500		499.5	*P 700		699.5	*P 1000		999.5			
P 355		354.5 ±2.54	*P 505		504.5	*P 710		709.5	*P 1020		1019.5			
P 360		359.5 ±2.57	*P 510		509.5	*P 720		719.5	*P 1040		1038.5			
*P 365		364.5 ±2.60	*P 515		514.5	*P 730		729.5	*P 1060		1059.5			
*P 370		369.5 ±2.63	*P 520		519.5	*P 740		739.5	*P 1080		1079.5			
P 375		374.5 ±2.67	*P 525		524.5 ±3.70	*P 750		749.5 ±5.30	*P 1100		1099.5			
P 380		379.5 ±2.70	*P 530		529.5	*P 760		759.5	*P 1120	1119.5				
P 385		384.5 ±2.73	*P 535		534.5	*P 770		769.5	*P 1140	1139.5				
*P 390		389.5 ±2.77	*P 540		539.5	*P 780		779.5	*P 1160	1159.5				
*P 395		394.5 ±2.79	*P 545		544.5	*P 790		789.5	*P 1180	1179.5				
P 400		399.5 ±2.82	*P 550		549.5	*P 800		799.5	*P 1200	1199.5				
*P 405		±0.15	404.5		*P 555	±0.15		554.5	*P 810	8.4	809.5	±0.20	*P 1220	1219.5
*P 410			409.5		*P 560			559.5	*P 820		819.5		*P 1240	1239.5
*P 415			414.5		*P 565			564.5	*P 830		829.5		*P 1260	1259.5 ±7.50
*P 420			419.5		*P 570			569.5	*P 840		839.5		*P 1280	1279.5
*P 425			424.5		*P 575			574.5 ±4.00	*P 850		849.5 ±6.00		*P 1300	1299.5
*P 430			429.5		*P 580			579.5	*P 860		859.5		*P 1320	1319.5
*P 435			434.5		*P 585			584.5	*P 870		869.5		*P 1340	1339.5
*P 440			439.5		*P 590			589.5	*P 880		879.5		*P 1360	1359.5
*P 445			444.5		*P 595			594.5	*P 890		889.5		*P 1380	1379.5
*P 450			449.5		*P 600			599.5	*P 900		899.5		*P 1400	1399.5
*P 455		454.5	*P 610		609.5	*P 910		909.5	*P 1420	1419.5				
*P 460		459.5	*P 620		619.5	*P 920		919.5	*P 1440	1439.5				
*P 465		464.5 ±3.30	*P 630		629.5 ±4.70	*P 930		929.5 ±6.70	*P 1460	1459.5				
*P 470		469.5	*P 640		639.5	*P 940		939.5	*P 1480	1479.5				
*P 475		474.5	*P 650		649.5	*P 950		949.5	*P 1500	1499.5				