

JIS-P O型圈的尺寸 (单位 : mm)			JIS-P O型圈的尺寸 (单位 : mm)			JIS-P O型圈的尺寸 (单位 : mm)			JIS-P O型圈的尺寸 (单位 : mm)					
公称编号	线径 C/S	内径 d	公称编号	线径 C/S	内径 d	公称编号	线径 C/S	内径 d	公称编号	线径 C/S	内径 d			
*P 330	8.4	329.5 ±2.39	*P 480	8.4	479.5 ±3.30	*P 660	8.4	659.5 ±4.70	*P 960	8.4	959.5			
P 335		334.5 ±2.42	*P 485		484.5	*P 670		669.5	*P 970		969.5			
P 340		339.5 ±2.45	*P 490		489.5	*P 680		679.5	*P 980		979.5 ±6.70			
*P 345		344.5 ±2.48	*P 495		494.5	*P 690		689.5	*P 990		989.5			
*P 350		349.5 ±2.51	*P 500		499.5	*P 700		699.5	*P 1000		999.5			
P 355		354.5 ±2.54	*P 505		504.5	*P 710		709.5	*P 1020		1019.5			
P 360		359.5 ±2.57	*P 510		509.5	*P 720		719.5	*P 1040		1038.5			
*P 365		364.5 ±2.60	*P 515		514.5	*P 730		729.5	*P 1060		1059.5			
*P 370		369.5 ±2.63	*P 520		519.5	*P 740		739.5	*P 1080		1079.5			
P 375		374.5 ±2.67	*P 525		524.5 ±3.70	*P 750		749.5 ±5.30	*P 1100		1099.5			
P 380		379.5 ±2.70	*P 530		529.5	*P 760		759.5	*P 1120	1119.5				
P 385		384.5 ±2.73	*P 535		534.5	*P 770		769.5	*P 1140	1139.5				
*P 390		389.5 ±2.77	*P 540		539.5	*P 780		779.5	*P 1160	1159.5				
*P 395		394.5 ±2.79	*P 545		544.5	*P 790		789.5	*P 1180	1179.5				
P 400		399.5 ±2.82	*P 550		549.5	*P 800		799.5	*P 1200	1199.5				
*P 405		±0.15	404.5		*P 555	±0.15		554.5	*P 810	8.4	809.5	±0.20	*P 1220	1219.5
*P 410			409.5		*P 560			559.5	*P 820		819.5		*P 1240	1239.5
*P 415			414.5		*P 565			564.5	*P 830		829.5		*P 1260	1259.5 ±7.50
*P 420			419.5		*P 570			569.5	*P 840		839.5		*P 1280	1279.5
*P 425			424.5		*P 575			574.5 ±4.00	*P 850		849.5 ±6.00		*P 1300	1299.5
*P 430			429.5		*P 580			579.5	*P 860		859.5		*P 1320	1319.5
*P 435			434.5		*P 585			584.5	*P 870		869.5		*P 1340	1339.5
*P 440			439.5		*P 590			589.5	*P 880		879.5		*P 1360	1359.5
*P 445			444.5		*P 595			594.5	*P 890		889.5		*P 1380	1379.5
*P 450			449.5		*P 600			599.5	*P 900		899.5		*P 1400	1399.5
*P 455		454.5	*P 610		609.5	*P 910		909.5	*P 1420	1419.5				
*P 460		459.5	*P 620		619.5	*P 920		919.5	*P 1440	1439.5				
*P 465		464.5 ±3.30	*P 630		629.5 ±4.70	*P 930		929.5 ±6.70	*P 1460	1459.5				
*P 470		469.5	*P 640		639.5	*P 940		939.5	*P 1480	1479.5				
*P 475		474.5	*P 650		649.5	*P 950		949.5	*P 1500	1499.5				

JIS-S		O型圈的尺寸 (单位 : mm)		
公称编号	线径 C/S	内径 d		
*S 2	1.5 ±0.10	1.5 ±0.15		
S 3		2.5		
S 4		3.5		
S 5		4.5		
S 6		5.5		
S 7		6.5		
S 8		7.5		
S 9		8.5		
S 10		9.5		
S 11.2		10.7		
S 12		11.5		
S 12.5		12.0		
S 14		13.5		
S 15		14.5		
S 16		15.5		
S 18		17.5		
S 20		19.5		
S 22		21.5		
S 22.4		2 ±0.10	21.9 ±0.15	
S 24			23.5	
S 25	24.5			
S 26	25.5			
S 28	27.5			
S 29	28.5			
S 30	29.5			

JIS-S		O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d	
S 31.5	2 ±0.10	31.0 ±0.15	
S 32		31.5	
S 34		33.5	
S 35		34.5	
S 35.5		35.0	
S 36		35.5	
S 38		37.5	
S 39		38.5	
S 40		39.5	
S 42		41.5	
S 44		43.5	
S 45		44.5	
S 46		45.5	
S 48		47.5	
S 50		49.5	
S 53		52.5 ±0.25	
S 55		54.5	
S 56		55.5	
S 60		59.5	
S 63		62.5	
S 65	64.5		
S 67	66.5		
S 70	69.5		
S 71	70.5 ±0.40		
S 75	74.5		

JIS-S		O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d	
S 80	2 ±0.10	79.5 ±0.40	
S 85		84.5	
S 90		89.5	
S 95		94.5	
S 100		99.5	
S 105		104.5	
S 110		109.5	
S 112		111.5	
S 115		114.5	
S 120		119.5	
S 125		124.5	
S 130		129.5	
S 132		131.5	
S 135		134.5	
S 140		139.5	
S 145		144.5	
S 150		149.5 ±0.60	
*S 155		154.5	
*S 160		159.5	
*S 165		164.5	
*S 170	169.5		
*S 175	174.5		
*S 180	179.5		
*S 185	184.5 ±0.80		
*S 190	189.5		

JIS-S		O型圈的尺寸 (单位 : mm)	
公称编号	线径 C/S	内径 d	
*S 195	2 ±0.10	194.5 ±0.80	
*S 200		199.5	
*S 205		204.5	
*S 210		209.5	
*S 215		214.5	
*S 220		219.5	
*S 225		224.5	
*S 230		229.5	
*S 235		234.5	
*S 240		239.5	
*S 245		244.5	
*S 250		249.5	
*S 255		254.5	
*S 260		259.5	
*S 265		264.5	
*S 270		269.5	
*S 275		274.5	
*S 280		279.5	
*S 285		284.5	
*S 290		289.5	
*S 295	294.5		
*S 300	299.5		

: 其他尺寸亦可提供 ! (单位 : 毫米/mm)